

E370 & S370 mains fed combination shower



Manufactured from Polyester-coated brass and Galvanised steel. Also available in stainless steel. Ideal for indoor installation or for areas where there is no risk of frost or overheating.

Available for non hazardous and hazardous areas.

KEY FEATURES

- 2-3 bar water supply pressure recommended to give unit 76 lpm
- 1 1/4" BSPF inlet & outlet
- Pull handle shower operation
- Push plate operation for eyebath
- Twin nozzles on eyebath with dust covers
- Rigid Pictorial Safety sign
- Manufactured to ANSI Z358.1-2009 specifications

MODELS AVAILABLE

E370 : manufactured from galvanised pipework (painted green) with brass valves. Plastic overhead shower rose and eyebath bowl.

S370 : manufactured from 304 stainless steel with stainless valves, overhead shower rose and eyebath bowl.

S370-316 : manufactured from 316 stainless steel with stainless valves, overhead shower rose and eyebath bowl.



Optional Extras		
Remote alarms	Alarm & Siren	Pendant Lamp
Shower walk on Platform	Scald Valve	Eyebath foot treadle
Pressure reg.valve	Flanged Inlets	Strainer



Certificate No. 6974

nooddouches.nl

Robbertsmatenstraat 15
8081 HL Elburg - Netherlands
Web: www.nooddouches.nl

Tel: +31 (0)525-686822
Fax: +31 (0)525-686133
Email: info@nooddouches.nl

Nooddouches.nl is a subsidiary of ZilvoldHF Trading BV